

ESENER

Power The World

Wall -mounted *Lithium battery*

51.2v10.24kwh

Power



100A

Discharge current



ESENER LITHIUM 51.2V 200Ah

- Advanced BMS with current limiting function
- CAN Bus, fully integrates and communicates with leading Inverter brands(Growatt,SOLAX,LUXPower,DEYE,MUST, Voltronic,Victron,SMA...etc.)
- Excellent high temperature performance
- High Cycle Life and Service Life
- High Energy Density and conversion efficiency
- Complete with integrated Battery Management System
- Compatible with most Inverters and chargers
- Low self discharge
- Easy wall mount or shelf rack installation
- Heavy duty side handles for easy handling and mounting on the wall
- Built in protection for over-charge, over-discharge & over-temperature



ITEM	SPECIFICATION		
Model	ES-10.24KWH		
Rated Capacity (5HR)	200 Ah		
Voltage	51.2 V		
Discharge Cut off Voltage	44.8 V		
Equalized Charge Voltage	56.8 V		
Max. Continuous Charging Current	100 A		
Max. Continuous Discharging Current	100 A		
C Rating	0.5 C		
Weight	Approx. 98 Kg		
Display	LCD		
Parallel	Parallel connection up to 15 packs with full communications		
Dimensions (WxDxH) mm	620mm x 590mm x 190mm		
Ports	1x CAN-bus, 1x RS-485 Battery Link ports, 2x Parallel Instruction ports		
Cells	New Li-ion Prismatic cells		
Warranty	5 Years		
Design Life	+/- 15 Years		
Cycle Life @ 0.5C	+/- 4000 Cycles @ 100% DOD, Above 6000 cycles @ 80% DOD		
Certification	CE, UN38.3, IEC, MSDS		
Outer Package Material	White bake lacquer steel case		
Operating Temperature	Charging: 0 to +50°C	Discharging: -10 to +50°C	Storage: -10 to +50°C
Protection	Electronic Circuit Breaker, BMS Voltage Protection, Current Limiting		
Compatible Inverter	Deye, Growatt, Sunsynk, Luxpower, ESENER, Victron, SMA, Voltronic...etc.		

* Due to continuous product improvements, specifications are subject to change without further notice.

All products are manufactured to the following standards:



ESENER

ADVANCED ENERGY STORAGE SYSTEMS



ES-10.24KWH