

SUN  SYNK®

SINGLE-PHASE HYBRID INVERTER



DATASHEET

SYNK-5K-SG04LP1-SM2

www.sunsynk.com
sales@sunsynk.com
customerservices@sunsynk.com

Model	SYNK-5K-SG04LP1-SM2	
Battery Input Data		
Battery Type	Lead-acid or Li-Ion	
Battery Voltage Range	40Vd.c ~ 60Vd.c	
Max. Charging/Discharging Current	120Ad.c	
Charging Strategy for Li-Ion Battery	Self-adaption to BMS	
Number of Battery Input	1	
PV String Input Data		
Max. PV Access Power	10000W	
Max. PV Input Power	8000W	
Max. PV Input Voltage	500V	
Start-up Voltage	125V	
PV Input Voltage Range	125~500V	
MPPT Voltage Range	150~425V	
Full Load MPPT Voltage Range	300~425V	
Rated PV Input Voltage	370V	
Max. Operating PV Input Current	18Ad.c + 18Ad.c	
Max. Input Short-Circuit Current	27Ad.c + 27Ad.c	
No. of MPPT/No. of Strings per MPPT	2/1+1	
Max. Inverter Backfeed Current to the Array	0	
AC Input/Output Data		
Rated AC Input/Output Active Power	5000W	
Max. AC Input/Output Apparent Power	5500VA	
Peak Power (Off-Grid)	2 times of rated power, 10 s	
Rated AC Input/Output Current	22.8/21.8Aa.c	
Max. AC Input/Output Current	25/24Aa.c	
Max. Continuous AC Passthrough (grid to load)	35A	
Max. Output Fault Current	50A	
Max. Output Overcurrent Protection	80A	
Rated Input/Output Voltage/Range	220 V/230 V 0.85Un-1.1Un	
Grid Connection Form	L+N+PE	
Rated Input/Output Grid Frequency/Range	50 Hz/45 Hz-55 Hz 60 Hz/55 Hz-65 Hz	
Power Factor Adjustment Range	0.8 leading to 0.8 lagging	
Total Current Harmonic Distortion THDi	<3% (of nominal power)	
DC Injection Current	<0.5% In	
Efficiency		
Max. Efficiency	97.60%	
Euro Efficiency	96.50%	
MPPT Efficiency	>99%	

Protection

Integrated	DC Polarity Reverse Connection Protection, AC Output Overcurrent Protection, AC Output Overvoltage Protection, AC Output Short Circuit Protection, Thermal Protection, DC Terminal Insulation Impedance Monitoring, DC Component Monitoring, Ground Fault Current Monitoring, Power Network Monitoring, Island Protection Monitoring, Earth Fault Detection, DC Input Switch, Overvoltage Load Drop Protection, Residual Current (RCD) Detection
Integrated (Optional)	Arc Fault Circuit Interrupter (AFCI)
Surge Protection Level	TYPE II (DC), TYPE II (AC)

Interface

Display	LCD+LED
Communication Interface	RS232/RS485/CAN
Monitor Mode	GPRS/WIFI/Bluetooth/4G/LAN (optional)

General Data

Operating Temperature Range	-40~60°C, >45°C Derating
Permissible Ambient Humidity	0~100%
Permissible Altitude	2000m
Noise	<30dB
Ingress Protection (IP) Rating	IP65
Inverter Topology	Non-Isolated
Over Voltage Category	OVC II (DC), OVC III (AC)
Net Weight	19kg
Cabinet Size (WxHxD)	376×470×241.5 mm (Excluding connectors and brackets)
Warranty	5 years (10 when installed with a Sunsynk battery)
Type of Cooling	Natural Cooling
Grid Regulation	NRS 097-2-1; Additional connections available upon request
EMC/Safety Regulation	IEC/EN 61000-6-1/2/3/4, IEC/EN 62109-1, IEC/EN 62109-2
Pollution Degree	PD2 (Inside) PD3 (Outside)
Manufacturer Country	China



NOTICE

Safe Transport and Handling of the Inverter

When transporting the equipment, always use its original packaging and keep it intact as a complete unit. Store the product in a dry environment, avoiding direct sunlight, and maintain a temperature range between -40°C and 60°C. As the equipment can be quite heavy, always consider its total weight when moving, transporting, or installing it, ensuring that the installation site has adequate load-bearing capacity. Transporting and installing the inverter should only be carried out by qualified personnel.



Contact Us

Call +44 151 832 4300 **Email** sales@sunsynk.com **Website** www.sunsynk.com

- Address**
- HK** Room 702-704, 7/F Texwood Plaza, 6 How Ming Street, Kwun Tong, Kowloon, Hong Kong
 - UK** Sunsynk UK Ltd, 17 Turnstone Business Park, Mulberry Avenue, Widnes, Cheshire, WA8 0WN
 - SA** Unit 2, 3 & 4, 80 Highview Blvd, Ferndale, Randburg, 2160, South Africa
 - NL** Sunsynk NL BV, Henri Wijnmalenweg 8, 5657 EP Eindhoven, Netherlands
 - AU** Level 1, 982-988 Wellington Street, West Perth WA 6005, Australia
 - ES** Tafetana, 32 P.I. Las Andoriñas 38639 Las Chafiras Santa Cruz de Tenerife
 - US** 100 S. Ashley Drive, Suite 600, Tampa, Florida, 33602, United States of America